



- Double hex key drive allowing maximum accessibility
- Ergonomically knurled bolt head for fast one-hand operation
- Large clamp range, 5 Tonne clamp force, 25 Tonne shear force
- High quality, through hardened steel, high precision ground finish
- Double O-Rings prevent simultaneous rotation when tightening and at the same time cleaning the system bores.
- 6 5 clamping balls, which are mechanically secured against falling out!
- TI Ergonomically designed allowing for multi-bolt corner interaction
- 8 Plus lifetime warranty!



Your benefits:

- Workpiece clamping true to position and location through adjustable spring loaded compensation
- Tension tube can be replaced quickly, available in different lengths
- With adjustment ring for height fixing
- Handle type can be changed
 - e.g. Hex, Tee, Toggle or pneumatic cylinder.
- 5 Foot pad can be exchanged. e.g. Stainless Steel, Plastic or Steel
- 6 Accepted by any Demmeler system bore (self-clamping effect)
- 71 Modular in construction
- Extendable, Retractable, 2 Position Clamping Range
- Plus lifetime warranty!



Your benefits:

- 1 Bessey handle with a special surface and rubberised inserts for rich and non-slip grip!
- 2 Additional handle types can be exchanged e.g. Hex, Tee, Toggle or Pneumatic cylinder
- Modularity down to detail: The Demmeler clamping bush can be used in any system bore. This allows for multiple clamping options in a few simple steps!
- Clamping handle can be tilted up to 15° at full power allowing enough room for welding!
- Foot pad can be exchanged and also be used in system bores as workpiece support, workpiece stop or small "V" block
- 6 Graphite impregnated spindle for maintenance free durability




We set the **Industry Standard in Clamping Systems**

D28 & D16 system for everyday weldments



The D28 ExpertLine is our preferred system for accurate fixturing






ExpertLine welding tables...

Your benefits at a glance:

- → Standard 4 hole pattern (Optional 5 & 9 Hole)
- → Sound technology for everyday use!
- → Grid lines every 100 mm
- With high fins and strongly ribbed, hence high intrinsic stability
- → Stable M24 x 2 threaded foot spindle ± 30 mm adjustable
- Modularly expandable in all five directions over the entire length, width and height
- Without measuring rule, it is possible to very quickly erect accurate clamping jigs
- Various foot type versions available
- Spatter free with use of ProtectDem solution
- → High precision tolerancing





P	roduct I	nfo			Article ID			
Presentation	L mm	W mm	H mm	Kg	Legs	Description	Item Code	
	1000	1000	220	368	4	Worktable 1000 x 1000 3D Demmeler	1001	
	1200	1200	220	474	4	Worktable 1200 x 1200 3D Demmeler	1001-2	
A I HEREE SEE	1500	1500	220	724	4	Worktable 1500 x 1500 3D Demmeler	1001-5	
	2000	1000	220	656	4	Worktable 2000 x 1000 3D Demmeler	1002	
in her there	2400	1200	220	914	6	Worktable 2400 x 1200 3D Demmeler	1003	
	3000	1500	220	1420	6	Worktable 3000 x 1500 3D Demmeler	1004	
	3000	1000	220	970	6	Worktable 3000 x 1000 3D Demmeler	1007	
Special sizes on request						Note: Table Item Codes shown do not include legs		
Presentation	Adjus	tment	Нm	ım	Kg	Description Item	Code	

*			
± 30 mm 630	9	Assy 3D Table Leg	1009-3D

Welcome to the family